SUN TV CHANNELS STB Tuning procedure - MEASAT M3D 91.5 DEG E

Following are the New frequency parameters kindly Re-Tune to the said frequency (as per attachment titled SUN TV network delivery Parameters).

Procedure to Re-Tune STB

- Step 1. Please be ready with new Satellite Measat M3D 91.5 Degree E-Vertical Polarity RF Cable, Input to the Dish Port .
- Step 2.Press Menu and Go to Defaults setting- input 0000 through remote
- Step 3. Press Menu
- Step 4. Go to Manual Scanning
- Step 5. To tune into Sun TV channels Enter **Frequency 4040** MHz and enter Ok.
- Step 6. All SUN TV channels **on Stream 1** frequency 4040 MHz will be automatically scanned and ready.
- Step 7. Select the Relevant SUN TV Channel for the STB
- Step 8. To receive SUN TV network channels on Stream 2 follow steps 1 to 4 and in Step 5 select frequency 4080 MHZ.
- Step 9. All SUN TV Channels on Stream 2 frequency 4080 MHz will be automatically scanned and ready
- Step 10. Select the relevant SUN TV Network channel on stream 2 in the STB.

PLEASE DO NOT REMOVE CAM AND/OR VC CARD FROM THE SLOT